

## FOLDING SLIDING DOORS ENQUIRY/ORDER FORM

Company: .....

Account No. ....

Address: .....

..... Postcode: .....

Tel: .....

Fax: .....

Contact Name: .....

Email: .....

Requested Delivery Date: .....  
*(Lead time of 10 working days)*

Order Reference: .....

Signature: .....

Page  of

Quote	
Order	

**FOLDING OPTIONS** (When viewed from outside)

**NB. Minimum sash width 550mm per pane, maximum sash width 1000mm per pane.**

Total number of leaves	Number of leaves folding left	Number of leaves folding right
For example: <b>3</b> Total number of door leaves	<b>1</b> Number of door leaves opening left	<b>2</b> Number of door leaves opening right

**DIMENSIONS**





**Overall width:**

.....  
*Maximum width: 6000mm*

**Overall height:**

.....  
*Maximum height: 2400mm*

**EXTERNAL STYLING**

<input type="checkbox"/> Pencil Round	
<input type="checkbox"/> Chamfered	
<input type="checkbox"/> Squared	
<input type="checkbox"/> Decorative	

**FRAME COLOUR**

<b>Internal:</b>	<b>External:</b>
<input type="checkbox"/> White	<input type="checkbox"/> White
<input type="checkbox"/> Cream	<input type="checkbox"/> Cream
<input type="checkbox"/> Grey	<input type="checkbox"/> Grey
<input type="checkbox"/> Black	<input type="checkbox"/> Black

**OPENING IN/OUT**

Open in     Open out

**HARDWARE**

Anodised Silver

Anodised Black

*Locks/keeps are Anodised Silver.  
Roller units are Black Anodised powder finish.*

**SILL TYPE** (Silver Anodised Aluminium)

<input type="checkbox"/> No sill	<input type="checkbox"/> Part M low threshold
<input type="checkbox"/> Standard threshold with 150mm sill	<input type="checkbox"/> Part M low threshold ramp/cover
<input type="checkbox"/> Integrated 120mm sill	<input type="checkbox"/> Part M low threshold ramp/ramp

**GLAZING BEAD**



Squared/Chamfered - 28mm - Chamfered Verticals

Squared/Squared - 28mm - 4 Sides

Squared/Squared - 44mm - 4 Sides

**GLAZING OPTIONS**

(All Toughened)

<input type="checkbox"/> Standard double glazed - 28mm (1.5 W/m <sup>2</sup> K U-value*)	<input type="checkbox"/>  Standard double glazed (Laminated) - 28mm (1.5 W/m <sup>2</sup> K U-value*)
<input type="checkbox"/> Celsius double glazed - 28mm (1.4 W/m <sup>2</sup> K U-value*)	
<input type="checkbox"/> Triple glazed - 44mm (1.0 W/m <sup>2</sup> K U-value*)	<input type="checkbox"/>  Triple glazed (Laminated) - 44mm (1.0 W/m <sup>2</sup> K U-value*)

*\*Figures quoted are whole door U-values based on BRFC standard bi-fold door*

**SKETCH YOUR DESIGN HERE:** (When viewed from outside)

Additional notes: .....

.....

.....

# warmcore<sup>®</sup> BY ORANGECORE

## FOLDING SLIDING DOORS ENQUIRY/ORDER FORM

### ORDER GUIDELINES

#### Maximum and Minimum Door Sizes

##### DOOR HEIGHTS

THRESHOLD	MINIMUM	MAXIMUM
Std	2020	2400
Integ sill	2020	2400
Part M LT	2000	2400

*NB: Heights noted do not include additional thermally broken sill.  
Allow 26.5mm for this if it is required.*

##### DOOR WIDTHS

STYLE	MINIMUM	MAXIMUM
220	1500	2000
330	1800	3000
321	1800	3000
440	3000	4000
431	2350	4000
422	3000	4000
550	2925	5000
541	2925	5000
532	2925	5000
660	4500	6000
651	3475	6000
642	4500	6000
633	3475	6000
770	4050	6000
761	4050	6000
752	4050	6000
743	4050	6000